

County Surveyor's Record, Douglas County, Oregon

Willamette Meridian through T. 27 S.

CHAINS

Mountainous or heavily timbered land or land covered
with dense undergrowth, 80.00 chs.

North, bet. secs. 7 and 12.

Ascend through heavy timber and dense undergrowth.

1.73 A fir, 40 ins. diam. on line I mark with 2 notches on
N. and S. sides.

4.25 Top of ridge point bears SE. and NW.
Thence along E. slope.

23.25 A spring branch, 4 lks. wide, good water, course S.75*E.
Ascend, bearing of hill S.50*E. N.50*W.

Difference between measurement of 40.00 chs. by two sets
of chainmen is 8 lks.; position of middle point,

By 1st set, 40.04

By 2nd set, 39.96, the mean of which is

40.00 Set a basalt stone 15x10x6 ins., 10 ins. in ground for $\frac{1}{4}$
sec. cor. marked with $\frac{1}{4}$ on W. face, from which

A fir, 18 ins. diam., bears SE. 17 lks. dist.
marked $\frac{1}{4}$ S 7 B T.

A fir, 26 ins. diam., bears S.68*W. 24 lks. dist.
marked $\frac{1}{4}$ S 12 B T.

41.00 Bearing of hill changes to E. and W.

62.00 Top of divide, 1500 ft. high, sudden descent over pre-
cipitous ground, bearing of hill, N. & S.

Difference between measurement of 80.00 chs. by two sets
of chainmen is 12 lks., position of middle point,

By 1st set, 80.06

By 2nd set, 79.94, the mean of which is

80.00 Set a basalt stone, 15x10x6 ins., 10 ins. in ground for
cor. of secs. 1, 6, 7 and 12, marked with 1 notch on
N. and 5 notches on S. edges, from which

A fir, 10 ins. diam., bears N.15*E. 16 lks. dist.
marked T 27 S R 1 E S 6 B T.

A fir, 8 ins. diam., bears S.85*E. 45 lks. dist.
marked T 27 S R 1 E S 7 B T.