

## County Surveyor's Record, Douglas County, Oregon

Willamette Meridian through T. 27 S.

CHAINS

Difference between measurement of 80.00 chs. by two sets of chainmen is 16 lks.; position of middle point,

By 1st set, 80.08

By 2nd set, 79.92, the mean of which is

80.00 Set a basalt stone, 20x18x12 ins., 15 ins. in ground for cor. of Tps. 26 and 27 S., Rs. 1 E. and 1 W. marked with 6 notches on each side, from which

A fir, 16 ins. diam., bears N.83\*E. 75 lks. dist. marked T 26 S R 1 E S 31 B T.

A fir, 24 ins. diam., bears S.21 $\frac{1}{2}$ \*E. 27 lks. dist. marked T 27 S R 1 E S 6 B T.

A fir, 20 ins. diam., bears S.55 $\frac{1}{2}$ \*W. 55 lks. dist. marked T 27 S R 1 W S 1 B T.

A fir, 24 ins. diam., bears N.61\*W. 48 lks. dist. marked T 26 S R 1 W S 36 P T.

Land, mountainous.

Soil, stony and 3rd rate.

Timber, fir, pine, laurel, and hemlock.

Undergrowth, laurel and hazel.

Mountainous or heavily timbered land or land covered with dense undergrowth, 80.00 chs.

July 7, 1902.

General Description

This line through its entire length runs across high mountains, ridges and divides and across streams having a westerly trend.

The land is of a mountainous and broken character, well watered and covered with fir, pine and hemlock timber. The land is chiefly valuable for its timber, grazing and mineral.