

County Surveyor's Record, Douglas County, Oregon

25

Subdivisions of T. 27 S. R. 1 W.
Same Deputy and Contract

CHAINS

From the cor. of secs. 35 and 36 on the 6th Standard
Parallel, S., which I established June 18, 1902,
I run

N.0°1'W. bet. secs. 35 & 36 .

Descend through heavy timber and dense undergrowth.

0.30 A spring branch, 3 lks. wide, course NW.

17.00 Same spring branch, 2 lks. wide, course N.20°E.

36.50 Same spring branch, 2 lks. wide, course N.20°E.

Ascend, hillside bears N.75°E. S.75°W.

40.00 Set a basalt stone, 15x12x12 ins., 10 ins. in ground for
 $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which

A hemlock, 12 ins. diam., bears S.65°E. 47 lks. dist.
marked $\frac{1}{4}$ S 36 B T.

A fir, 10 ins. diam., bears N.50 $\frac{1}{2}$ °W. 17 lks. dist.
marked $\frac{1}{4}$ S 35 B T.

56.75 Top of ridge, bears N.50°E. S.50°W.

Descend

75.00 Foot of descent.

75.40 A creek, 15 lks. wide, course N.40°W.

80.00 Set a basalt stone, 15x10x8 ins., 10 ins. in ground for
cor. of secs. 25, 26, 35 and 36, marked with 1 notch
on S. and E. edges, from which

A cedar, 18 ins. diam., bears N.10°E. 38 lks. dist.
marked T 27 S R 1 W S 25 B T.

A hemlock, 20 ins. diam., bears S.39 $\frac{1}{2}$ °E. 41 lks. dist.
marked T 27 S R 1 W S 36 B T.

A cedar, 10 ins. diam., bears S.78°W. 28 lks. dist.
marked T 27 S R 1 W S 35 B T.

A fir, 16 ins. diam., bears N.17°W. 55 lks. dist.
marked T 27 S R 1 W S 26 B T.

Land, mountainous.

Soil, 3rd and 4th rates.

Timber, fir, hemlock, cedar and pine.