

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 27 S., R. 1 W.

CHAINS

40.00 Set a basalt stone, 20x12x10 ins., 15 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which
 A cedar, 10 ins. diam., bears N.25*E. 11 lks. dist. marked $\frac{1}{4}$ S 24 B T.
 A fir, 8 ins. diam., bears N.36*W. 51 lks. dist. marked $\frac{1}{4}$ S 23 B T.

69.65 A spring branch, 5 lks. wide, course NE.

80.00 Set a basalt stone, 15x12x8 ins., 10 ins. in ground for cor. of secs. 13, 14, 23 and 24, marked with 3 notches on S. and 1 notch on E. edges, from which
 A fir, 30 ins. diam., bears NE. 27 lks. dist. marked T 27 S R 1 W S 13 B T.
 A fir, 18 ins. diam., bears S.28*E. 22 lks. dist. marked T 27 S R 1 W S 24 B T.
 A fir, 18 ins. diam., bears S.40*W. 35 lks. dist. marked T 27 S R 1 W S 23 B T.
 A fir, 18 ins. diam., bears N.57*W. 40 lks. dist. marked T 27 S R 1 W S 14 B T.

Land, mountainous.

Soil, 4th rate.

Timber, fir, hemlock, pine and cedar.

Undergrowth, laurel and huckleberry.

Mountainous or heavily timbered land or land covered with dense undergrowth 80.00 chs.

S.89*44'E. on a random line bet. secs. 13 and 24.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.80 Intersect Will. Mer. 50 lks. S. of cor. of secs. 13, 18, 19 and 24.

Thence I run

S.89*55'W. on a true line bet. secs. 13 and 24.

Descend through heavy timber and dense undergrowth.

29.00 Foot of descent.

A spring branch, 5 lks. wide, course N.