

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 27 S., R. 1 W.

CHAINS	<p>Thence I run West, on a true line, bet. secs. 23 and 26. Along S. slope through heavy timber and dense undergrowth.</p> <p>25.00 Top of spur, 500 ft. high. Descend.</p> <p>40.25 Set a basalt stone, 15x10x5 ins., 10 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, from which A fir, 30 ins. diam., bears N.43*E. 37 lks. dist. marked $\frac{1}{4}$ S 23 B T. A cedar, 18 ins. diam., bears S.40*W. 34 lks. dist. marked $\frac{1}{4}$ S 26 B T.</p> <p>42.50 Bottom of ravine, course S. Ascend.</p> <p>55.00 Top of ascent; thence along S. slope.</p> <p>80.50 The cor. of secs. 22, 23, 26 and 27. Land, mountainous. Soil, 4th rate. Timber, fir, hemlock, pine and laurel. Undergrowth, laurel. Mountainous or heavily timbered land or land covered with dense undergrowth, 80.50 chs.</p> <p style="text-align: right;">July 16, 1902.</p>
	<p>At the cor. of secs. 22, 23, 26 and 27. Thence I run N.0*2'W. bet. secs. 22 and 23. Ascend through heavy timber and dense undergrowth.</p> <p>30.00 Top of divide, 1000 ft. high, bears E. and W. Descend.</p> <p>40.00 Set a basalt stone, 20x15x14 ins., 15 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which A fir, 12 ins. diam., bears N.84*E. 28 lks. dist. marked $\frac{1}{4}$ S 23 B T. A fir, 10 ins. diam., bears SE. 21 lks. dist. marked $\frac{1}{4}$ S 22 B T.</p>