

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 27 S., R. 1 W.

CHAINS

N. 0\*2' W. bet. secs. 15 and 16.

Ascend through heavy timber and dense undergrowth.

.14 A fir, 20 ins. diam. on line. I mark with 2 notches on N. and S. sides.

34.50 A perpendicular bluff, 25 ft. high; thence over precipitous ground.

40.00 The point for  $\frac{1}{2}$  sec. cor. falls on precipitous ground on an insecure place.

39.00 On line set a basalt stone, 12x10x6 ins., 8 ins. in ground for witness cor. to  $\frac{1}{2}$  sec. cor. marked W. C.  $\frac{1}{4}$  on W. face, from which

A fir, 30 ins. diam., bears N.70\*E., 43 lks. dist. marked W C  $\frac{1}{4}$  S 15 B T.

A maple, 10 ins. diam., bears N.66\*W., 58 lks. dist. marked W C  $\frac{1}{4}$  S 16 B T.

Thence over crags, over which I cannot chain.

To get the distance I offset as follows:

East 1.65 chs.

North 2.50 chs.

West 1.65 chs., to a point on line at

~~41~~.50 Top of crags.

Ascend.

45.00 Top of divide, 1500 ft. high, bears SE. and NW.

Thence over plateau.

67.50 A spring branch, 1 lk. wide, course S.75\*E.

Ascend.

80.00 Set a basalt stone, 20x12x4 ins., 15 ins. in ground for cor. of secs. 9, 10, 15 and 16 marked with 4 notches on S. and 3 notches on E. edges, from which

A fir, 12 ins. diam., bears N.75\*E., 36 lks. dist. marked T 27 S R 1 W S 10 B T.

A fir, 30 ins. diam., bears S.80\*E., 54 lks. dist. marked T 27 S R 1 W S 15 B T.