

East Boundary of Township 27 S., R. 3 W.
As surveyed by Sam C. Flint, U. S. Deputy Surveyor
under Contract No. 454, dated June 19, 1882.

CHAINS

From the corner of Townships 27 and 28 S., Ranges 2 and 3 W., I ran North, on a Random line bet. Rs. 2 and 3 W and set temp. mile and half mile posts and intersected the North bdy. of tp. line at 5 miles, 79 chs. and 15 lks. and the falling to be 288 lks. West from cor. to Tps. 26 and 27 S, Ranges 2 and 3 W.

The correction for the true line will therefore be 48 lks. West per mile and it's course S.0°21'W.

At the cor. of Tps. 26 and 27 S and Rs. 2 and 3 W is a Fir post, 4 ft. long, 4 ins. sq., set firmly in the ground and marked T 27 S R 2 W S 6 SE; T 26 S R 3 W S 36 NW; T 27 S R 3 W S 1 SW, from which

A Laurel, 12 ins. diam., bears S.5°E., 66 lks. dist., marked T 27 S R 2 W S 6 B T.

A Laurel, 5 ins. diam., bears N.25°W., 59 lks. Dist., marked T 26 S R 3 W S 36 B T.

A Fir, 16 ins. diam., bears S.38°W., 7 lks. dist., marked T 27 S R 3 W S 1 B T.

Thence I run S.0°21'W., on true line bet. Secs. 1 and 6.

Va. 18°30'E.

- 4.15 Rocky ridge perpendicular cliffs, course of ridge SE and NW.
- 39.15 Set Chinquapin post 3 ft. long, 4 ins. sq., firmly in the ground for $\frac{1}{2}$ Sec. cor. marked on E and W faces $\frac{1}{2}$ S, from which
- A Laurel, 5 ins. diam., bears N.15°W., 36 lks. dist., marked $\frac{1}{2}$ S B T.
- A Fir, 36 ins. diam., bears N.35°E., 42 lks. dist., marked $\frac{1}{2}$ S B T.
- 79.15 Set Oak post, 4 ft. long, 4 ins. sq. firmly in the ground and marked T 27 S R 2 W S 6 on NE; T 27 S R 3 W S 1 on NW; R 2 W S 7 on SE; R 3 W S 12 on SW with