

Sixth Standard Parallel South, R. 2 W.
 As surveyed by Samuel C. Flint, Deputy Surveyor,
 under Contract No. 459, dated August 3, 1882.

CHAINS

Began at Standard Corner of Township 27 S, Ranges 2 and 3 W, which is a post 4 ins. sq. and marked S C T 27 S on N, R 2 W S 31 on E and R 3 W S 36 on W faces, with 6 notches on NE and W faces, from which

A Fir, 12 ins. diam., bears N.43°E., 70 lks. dist., marked T 27 S R 2 W S 31 B T.

A Fir, 30 ins. diam., bears N.55°W., 46 lks. dist., marked T 27 S R 3 W S 36 B T.

A Fir, 36 ins. diam., bears S.25°W., 42 lks. dist., marked T 28 S R 3 W S 1 B T.

Thence I run

East, on S boundary S 31.

Va. 20°E.

- 3.00 Summit of Peaks Hill.
- 40.00 Set Cedar post 3 ft. long, 3 ins. sq., 24 ins. in the ground for standard $\frac{1}{4}$ Sec. cor. marked on N face S C $\frac{1}{4}$ S, from which
 - A Fir, 18 ins. diam., bears S.40°W., 29 lks. dist., marked S C $\frac{1}{4}$ S B T.
 - A Fir, 24 ins. diam., bears N.10°E., 18 lks. dist., marked S C $\frac{1}{4}$ S B T.
- 45.00 Spring branch 3 lks. wide, course S.
- 50.00 Commenced to ascend mountain.
- 80.00 Set Cedar post 4 ft. long, 4 ins. sq. 24 ins. in the ground for standard cor. to Secs. 31 and 32, marked T 27 S R 2 W on N, S 32 on E and S 31 on W faces, with 5 notches on the East 1 on the W edges, from which
 - A Fir, 24 ins. diam., bears N.15°E., 38 lks. dist., marked T 27 S R 2 W S 32 B T.
 - A Fir, 30 ins. diam., bears N.50°W., 17 lks. dist., marked T 27 S R 2 W S 31 B T.
 - A Fir, 30 ins. diam., bears S.47°W., 25 lks. dist., marked T 28 S R 2 W Sec. 6 B T.