

## Sixth Standard Parallel South, R. 2 W.

CHAINS

2 W, marked S C T 27 S on N, R 1 W S 31 on E, and  
R 2 W S 36 on W with 6 notches on N, E and W faces,  
from which

A Fir, 12 ins. diam., bears N.10°E., 41 lks.

dist., marked T 27 S R 1 W S 31 B T.

A Fir, 24 ins. diam., bears N.55°W., 16 lks.

dist., marked T 27 S R 2 W S 36 B T.

A Fir, 30 ins. diam., bears S.35°W., 30 lks.

dist., marked T 27 S R 2 W S 1 B T.

This township corner is located on S side of a rocky  
mountain 4000 ft. high; land on this mile is 3rd and  
4th rate, densely covered with Fir, Cedar and Hemlock,  
with a thick undergrowth of Vinemaple and Hazel.

August 22, 1862.

---

East Boundary of T. 27 S., R. 2 W.  
Same Deputy and Contract.

---

From the cor. of Tps. 27 and 28 S and Ranges 1 and 2 W  
I run N on Random line bet. Ranges 1 and 2 W and set  
temp. mile and half mile posts and intersected the  
North boundary of township line at 6 miles and 75 lks.  
and the falling was 10 lks. West from cor. to T 26  
and 27 S, Rs. 1 and 2 W.

The correction of the true line will therefore be 1-2/3  
lks. W per mile and its course will be S.0°01'W.

At corner is Chinquapin post, 4 ft. long, 4 ins. sq.,  
and marked T 26 S S 31 on NE, R 1 W S 6 on SE, T 27  
S S 1 on SW and R 2 W S 36 on NW faces, with 6  
notches on N, S, E and W edges, from which

A Laurel, 7 ins. diam., bears N.45°E., 28 lks.

dist., marked T 26 S R 1 W S 31 B T.