

# County Surveyor's Record, Douglas County, Oregon

East Boundary of Sec. 12, Tp. 27 S., R. 2 W., as  
Surveyed by Charles E. Roberts, U.S. Deputy Surveyor,  
Under Contract No. 759, dated Oct. 26, 1904.

CHAINS

At the cor. of secs. 1 and 12, on the range line,  
which is a basalt stone, 5 x 6 x 8 ins. above  
ground, marked and witnessed by the surveyor  
general.

Thence I run,  
South, on E. bdy. of sec. 12.

Through scattering timber and dense undergrowth.

9.24 Intersect closing cor. to secs. 6 and 7, Tp. 27 S.,  
R. 1 W., which is a basalt stone, firmly set,  
8 x 10 x 12 ins. above ground, marked:

CC on E. side, with  
5 grooves in S. face, and  
1 groove on N. face;

from which,

A fir, 12 ins. diam., bears S. 12°E., 45 lks.  
dist., marked: C C T 27 S R 1 W S 7 BT.

A maple, 7 ins. diam., bears N. 52°E., 40 lks.  
dist., marked: C C T 27 S R 1 W S 6 BT.

14.00 Begin to desc. hill, sloping to SW.

29.47 Settlers' trail, bears E. and W.

40.00 Set a basalt stone, 18 x 12 x 12 ins., 12 ins. in the  
ground, for 1/4 sec. cor., marked:

1/4 on W. face;

from which,

A fir, 16 ins. diam., bears N. 60°W., 25 lks.  
dist., marked: 1/4 S 12 BT.

A fir, 20 ins. diam., bears S. 68°W., 28 lks.  
dist., marked: 1/4 S 12 BT.

49.35 Intersect 1/4 sec. cor., to sec. 7, T. 27 S., R. 1 W.,  
which is a basalt stone, 7 x 7 x 12 ins. above ground,  
marked and witnessed as described by the surveyor  
general.

53.50 Spring branch, 3 lks. wide, course SW.

65.35 Klamath Trail, bears NW. and SE.

65.90 Little River, 100 lks. wide, good water; course NW.