

County Surveyor's Record, Douglas County, Oregon

East Boundary of Sec. 12, Tp. 27 S., R. 2 W.

CHAINS

74.00

Begin to asc.

80.00

Set a basalt stone, 15 x 8 x 6 ins., 10 ins. in the ground, for cor. of secs. 12 and 13, marked with:

4 notches on S., and
2 notches on N. edge;

from which,

A cedar, 7 ins. diam., bears S. 38°W., 31 lks.

dist., marked: T 27 S R 2 W S 13 BT.

A fir, 50 ins. diam., bears N. 40°W., 35 lks.

dist., marked: T 27 S R 2 W S 12 BT.

The cor. of secs. 7 and 18, Tp. 27 S., R. 1 W., which is a basalt stone, 8 x 7 x 6 ins. above the ground, marked and witnessed as described by the surveyor general, bears South, 10.10 chs.

I destroy marks on bearing trees referring to secs. 12 and 13.

Land; mountainous.

Soil; rocky, 2nd. and 4th. rate.

Timber; fir, pine and cedar.

Undergrowth; young fir, madrone and hazel.

Mountainous land and covered with dense undergrowth, 80.00 chs.

July 15, 1905.

(Omission in Records, supplied through Regional Forest Office, and copied by Ira F. Rankin, April 26, 1937.)