

County Surveyor's Record, Douglas County, Oregon

34

Subdivisions of T.27 S., R 2 W.

CHAINS

dist., Marked T 27 S R 2 W S 15 B T

A Fir, 36 ins. diam., bears S.52 $\frac{1}{2}$ *W., 126 lks. dist.,

Marked T 27 S R 2 W S 16 B T

A Fir, 30 ins. diam., bears N.88*W., 45 lks. dist.,

Marked T 27s R2 W S 9 B T

Land mountainous and rolling

Soil, rocky 3rd. & 4th. rate

Timber, Fir, Pine, Cedar and Hemlock

Undergrowth young Fir, and Vinemaple

Heavily timbered land or covered with dense undergrowth

80.00 chs.

SEE INSERT
4890 A

At the cor. of secs. 9, 10, 15 & 16

Thence I run

N.6*2'W., on a random line bet. secs. 9 & 10

40.00 Set Temp. $\frac{1}{4}$ sec. cor.

80.70 Intersect C C for secs. 9 & 10 set by me July 21, 1905

Thence I run

S.0*2'E., on a true line bet. secs. 9 & 10

Over rolling land through old slashing

2.25 G. Gustarsons Cabin bears E 80 lks.

5.40 Wagon Road to Peel bears SW and NE

6.00 Right bank of Little River, 125 lks. wide, course SW

19.25 Leave old slashing enter scattering timber and dense
undergrowth40.70 Set a basalt stone 14x8x5 ins. 10 ins. in the ground for
 $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W face from whichA White Fir, 10 ins. diam., bears S.73 $\frac{3}{4}$ *W., 22 $\frac{1}{2}$ lks.
dist., Marked $\frac{1}{4}$ S 9 B T.

A Madrone, 10 ins. diam., bears S.37*E., 22 lks. dist.

Marked $\frac{1}{4}$ S 9 B TI destroy $\frac{1}{4}$ sec. cor. and marks on bearing trees made
July 21, 1905

55.60 Spring Branch 2 lks. wide course NW

80.70 The cor. of secs. 9, 10, 15 & 16

Land rolling

1907