

County Surveyor's Record, Douglas County, Oregon

41

Retracements of Subdivisions of T. 27 S., R. 2 W.

CHAINS

44.00 Little River, 125 lks. wide, course NW.
 51.75 Spring branch 2 lks. wide, course North.
 80.44 Fall 90 lks. S of the cor. of Secs. 1, 2, 11 and 12,
 which is a badly decayed post and as three of the
 witness trees had fallen I reestablish this cor. by
 setting in place of old post a Basalt stone, 18x16x14
 12 ins.
 ins./in the ground, marked with 5 notches on S and 1
 notch on E edge, from which

A Hemlock, 12 ins. diam., bears N.21*E., 48 lks.
 dist., marked T 27 S R 2 W S 1 B T.

A Fir, 12 ins. diam., bears S.79*E., 46 lks.
 dist., marked T 27 S R 2 W S 12 B T.

A Fir, 10 ins. diam., bears S.39*W., 54 lks.
 dist., marked T 27 S R 2 W S 11 B T.

A Cedar, 22 ins. diam., bears N.20*W., 24 lks.
 dist., marked T 27 S R 2 W S 2 B T.

The course of the line from the $\frac{1}{4}$ Sec. cor. to the Sec.
 cor. is N.88*38'W., length 40.34 chs.

Land, mountainous and rolling.

Soil, rocky, 3rd and 4th rate.

Timber, Fir, Pine, Cedar and Hemlock; undergrowth young
 Fir and Vinemaple.

Mountainous land and covered with dense undergrowth.

80.44 chs.

July 16, 1905.

At the cor. of Secs. 1, 2, 11 and 12.

Thence I retrace

West, bet. Secs. 2 and 11.

Over rolling land through heavy timber and dense under-
 growth.

40.40 Fall 30 lks. S of $\frac{1}{4}$ Sec. cor. which is a post 3 ins. sq.,
 2 ft. above the ground firmly set, marked and witnessed
 as described by the Surveyor General.

The course of the line from Sec. cor. to the $\frac{1}{4}$ Sec. cor.