

County Surveyor's Record, Douglas County, Oregon

118

Retracement of the 6th. Standard Par. through R. 2 W.

CHAINS	<p>all bearing trees and remark A P B T. The course of this line is N.87°07'W., and the length is 40.65 chs.</p> <p>Land Mountainous</p> <p>Soil, 2nd. rate</p> <p>Timber, heavy Fir and Hemlock</p> <p>Dense undergrowth, Little Fir and Hemlock</p> <p>Sky overcast at noon; lat. observation impossible</p> <p style="text-align: right;">September 10, 1911</p>
1.72	<p>At the Standard cor. of secs. 34 and 35</p> <p>Thence I run</p> <p>West, retracing the S bdy. of sec. 34</p> <p>Ascend through heavy timber and dense underbrush</p> <p>The closing cor. of secs. 2 and 3, T. 28 S., R. 2 W., which is a post, firmly set, marked and witnessed as described by the Surveyor General bears North 3 lks.</p>
24.00	<p>Top of ridge, bears N & S</p> <p>Descend</p>
40.30	<p>The Standard $\frac{1}{4}$ sec. cor. which is a post firmly set, marked and witnessed as described by the Surveyor General bears North 60 lks. dist. I now change this cor. to an angle point as follows. Cut out all marks, and remark A P on N face; then cut out all bearing trees and remark A P B T. The course and distance of this line is N.89°09'W., 40.30 chs.</p>
57.65	<p>Creek, 2 lks. wide, course SW</p>
59.42	<p>Creek, 2 lks. wide, course SW</p>
80.57	<p>Creek, 1 lk. wide, course SE</p>
80.67	<p>The Standard cor. of secs. 33 & 34 which is a post firmly set, marked and witnessed as described by the Surveyor General bears S. 85 lks. dist. I now change this cor. to an angle point as follows: Cut out all maks and mark A P on N face then cut out all bearing trees and remark A P B T. The course and distance of this line, from the $\frac{1}{4}$ sec. cor. is S.87°57'W., 40.40 chs.</p> <p>Land Mountainous</p>