

County Surveyor's Record, Douglas County, Oregon

105

Extensions Survey of Subdivisions of T.27 S., R. 2 W., W.M.

CHAINS

more than nine years; has a good log cabin, barn 18x25 ft. and good out buildings. He has 8 acres cleared and in Timothy grass, has a good garden, similar to I.L. Bourgeois. These are the only two settlers in this township.

Morris Wygant
Compassman for Zachariah M. Derrick
U.S. Deputy Surveyor

October 31, 1911

Subdivisions of T. 28 S., R. 2 W.
William N. Gibb, Deputy Surveyor, under Contract No. 783
Dated December 3, 1908

40.65 Thence from cor. secs. 31 & 32, I retrace E. along 6th. Standard Parallel on S. bdy. sec. 32., T. 27 S., R. 2 W. $\frac{1}{2}$ sec. cor. which is a stake marked and witnessed as described by the Surveyor Genral.

81.29 Cor. secs. 32 & 33, which is a stake marked and witnessed as as described by the Surveyor General

Note: Distances given in this mile are the mean of two separate measurements.

Part of
Retracement and Resurvey of/Sixth Standard Parallel South,
Through Range 2 West
Fred Mensch, U.S. Cadastral Engineer, under Special
Instructions, dated June 7th, 1922.

43.34 From the Standard corner of Tps. 27 S., Rs. 1 & 2 W. West, retracing the South bdy. of sec. 36 Intersect the Standard $\frac{1}{2}$ sec. cor.

82.91 Fall, 15 lks. N. of the Standard cor. of secs. 35 & 36

From the Standard corner of Tps. 27 S., Rs. 1 & 2 W., which is a basalt stone, 12x10x5 ins. above ground, firmly set, marked S C on N., with 6 grooves on N., E., and W. faces from which

A Fir, 16 ins. diam., bears N.71*W., 62 lks. dist.,
Marked T 27 S R 2 W S 36 S C B T; old B T

No tree available for bearing tree, in sec. 31: Raise a