

Retracement and Resurvey of Sixth Standard Parallel South  
Through Range 2 West

CHAINS

mound of stone, 3 ft. base, 1½ ft. high N. of cor.

West resurveying the South boundary of sec. 36

Over Mountainous land, through heavy timber and dense  
undergrowth

Descend 185 feet

6.27 The closing cor. of Tps. 28 S., Rs. 1 & 2 W., already  
described

12.66 Rocky Canyon, course S., Ascend 350 ft. to

21.75 Top of Red Butte, bears S. 12.80 chs. dist.

23.85 Spur, slopes N., continue along NE. slope; Ascend 100 ft.  
to standard ¼ sec. cor.

35.83 Old Trail to Red Butte Lookout, bears N &amp; S

42.13 Trail to Red Butte Lookout, bears NE &amp; SW

43.34 The standard ¼ sec. cor., which is a sound Fir Post, 4 ins.  
sq., 12 ins. above ground, firmly set, marked S C ¼ S  
36 on N face from which

A Fir, 36 ins. diam., bears N.5°E., 13 lks. dist.,

Marked S C ¼ S 36 B T ; old bearing tree

This appears to be the original bearing tree established by  
Flint, shown in the old notes as S.30°E., which bearing I  
conclude to be an error of the original notes. The other  
old bearing tree is not found

A Fir, 24 ins. diam., bears N.20°W., 142 lks. dist.,

Marked S C ¼ S 36 B T; new bearing tree

Thence

S.89°47'W.

Descend 275 ft. over NW. slope to spur

4.70 A Point, 40.00 chs. E. of the closing cor. of secs. 1 &  
2, determined as hereinafter set forth; set an iron  
post, 3 ft. long, 1 in. diam., 27 ins. in the ground,  
for ¼ sec. cor. of sec. 1, only with brass cap marked

S I

1923

from which