

168

Retracement and Resurvey of Sixth Standard Parallel S.,
through R. 2 W.

CHAINS

Descend 150 ft. over W. slope to

- 0.22 Trail to Red Butte Lookout, bears NW., and SE.
- 5.13 Point of intersection of line bet. secs. 1 & 2, as herein-
after set forth; set an iron post, 3 ft. long, 2 ins.
diam., 27 ins. in the ground, for closing cor. of secs. 1
& 2 with brass cap marked

T 27 SR2WS35

S 2	S 1
-----	-----

T28S	R2W
------	-----

C C
1923

from which

A Fir, 6 ins. diam., bears S.68½°E., 223 lks. dist.

Marked T 28 S R 2 W S 1 C C B T

A Fir, 9 ins. diam., bears S.5°W., 114 lks. dist.,

Marked T 28 S R 2 W S 2 C C B T

Continue to descend over W slope

- 8.90 Trail, Peel to Red Butte, bears NW and SE
- 12.26 Brook, 3 lks. wide, course SW
- 13.00 Descend SW slope
- 27.20 Draw, opens S., 510 ft. lower than Standard Sec. cor.
Ascend 100 ft. over E. slope
- 32.54 Spur, slopes S., leave burn, enter green timber, bears
N & S., Descend 50 ft. over SW slope
- 35.50 Draw opens SW., Ascend 100 ft. over SW slope to
- 40.45 The Angle Point, which is a sound Yew Post, 4 ins. sq.,
12 ins. above ground, marked ½ S 35 on N face. I destroy
the marks on the Post, and remark A P on N. face. The
bearing trees are as described in the Notes of the Flint
survey, but as the tree N. of line is now decayed and
not suitable for permanent witness, I destroy the marks
on both the old trees; from the post
A Hemlock, 24 ins. diam., bears N.67°E., 21 lks. dist.,
Marked A P B T; new bearing tree
A Yew, 7 ins. diam., bears N.17°W., 16 lks. dist.,
Marked A P B T; new bearing tree