

County Surveyor's Record, Douglas County, Oregon

109

Retracement and Resurvey of Sixth Standard Parallel S.,
through Range 2 W.

CHAINS

Thence N.88°3'W., on a true line

Ascend 50 ft. to

.4.00 Spur, slopes S; Descend 250 ft. over SW., slope to closing
sec. cor.4.70 A Point, 40.00 chs. West of the closing cor. of secs. 1 &
2; set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for $\frac{1}{2}$ sec. cor., of sec. 2 only with brass
cap marked $\frac{1}{2}$ S 2

1923

from which

A Fir, 40 ins. diam., bears S.41°E., 54 lks. dist.,

Marked $\frac{1}{2}$ S 2 B T

A Yew, 10 ins. diam., bears S.16°W., 28 lks. dist.,

Marked $\frac{1}{2}$ S 2 B T

9.50 Ravine, course S; Ascend 20 ft. to

10.50 Spur, slopes S; Descend 250 ft. over SW slope

31.54 A Trail, bears NW and SE. Foot of descent bears NW & SE
Thence over gently rolling land, slopes S.39.22 The closing cor. of secs. 34 & 35, which is a sound Fir
Post, 4 ins. sq., 12 ins. above ground, marked C C T
27 S R 2 W on N., S 35 on E., and S 34 on W. face from
which

A Cedar, 30 ins. diam., bears N.45°E., 11 lks. dist.

Marked T 27 S R 2 W S 35 C C B T; old B T

A Fir, 36 ins. diam., bears N.78°W., 92 lks. dist.,

Marked T 27 S R 2 W S 34 C C B T; old B T

41.02 Angle Point, located by record measurement from the original
bearing trees, no other evidence found. At exact angle
point; set a Cedar Post, 3 ft. long, 4 ins. sq., 24 ins.
in the ground marked A P on N face from which

A Fir, 24 ins. diam., bears N.56°E., 30 lks. dist.,

Marked A P B T; old bearing tree

A Fir, 28 ins. diam., bears N.4°W., 13 lks. dist.,

Marked A P B T ; old bearing tree

No iron post or stone of sufficient size is available