

Resurvey of E. Bdy. of T. 27 S., R. 4 W.

CHAINS

I commence at the cor. of secs. 25, 30, 31 and 36, on the E. Bdy. of the Tp., and run

North, retracing the line bet. Rs. 3 and 4 W., making careful and diligent search at each 40.00 and 80.00chs. for  $\frac{1}{4}$  sec. and sec. cors., and setting temp. cors.; and at 403.47 chs. fall 143 lks. W. of the cor. of Tps. 26 and 27 S., Rs. 3 and 4 W., which is an oak post, 4 ins. square and 6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General, except The SW. bearing tree, which has disappeared. The bearing trees are as follows:

- A W. Oak, 10 ins. dia., bears N.8°E., 569 lks. dis.  
mkd. T 26 S R 3 W S 31 B T. (original B. T.)
- A W. Oak, 28 ins. dia., bears S.20°E., 825 lks. dis.  
mkd. T 27 S R 3 W S 6 B T. (original B. T.)
- A W. Oak, 10 ins. dia., bears S.75°45'W., 265 lks. dis.  
mkd. T 27 S R 4 W S 1 B T. (new B. T.)
- A W. Oak, 12 ins. dia., bears N.36°W., 165 lks. dis.  
mkd. T 26 S R 4 W S 36 B T. (original B. T.)

Returning to the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., which is a badly decayed post, marked and witnessed as described by the Surveyor General, except the NE. and NW., bearing trees, which have disappeared. I perpetuate this cor. as follows:  
Alongside the old post,

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with the brass cap marked

|      |     |
|------|-----|
| T27S |     |
| R4W  | R3W |
| S25  | S30 |
| S36  | S31 |
| 1917 |     |

from which

- A Cedar, 40 ins. dia., bears N.45°30'E., 50 lks. dis.  
mkd. T 27 S R 3 W S 30 B T. (new B. T.)
- A Cedar, 26 ins. dia., bears S.45°E., 23 lks. dis.  
mkd. T 27 S R 3 W S 31 B T. (original B. T.)
- A Cedar, 32 ins. dia., bears S.23°15'W., 31 lks. dis.  
mkd. T 27 S R 4 W S 36 B T. (original B. T.)