

Resurvey of E. Bdy. of T. 27 S., R. 4 W.

CHAINS	
	A Hemlock, 12 ins. diam., bears N.28*W., 28 lks. dist. mkd. T 27 S R 4 W S 25 B T. (New B. T.)
	Thence
	N.0*12'E., resurveying the line bet. secs. 25 and 30.
	Ascend S. slope through heavy timber and dense undergrowth.
9.00	Spur slopes SW., continue ascent along W. slope.
19.00	Spur slopes W., 140 ft. above sec. cor., descend NW. slope.
25.00	Creek, 2 lks. wide, course SW., 80 ft. below spur. Ascend SE. slope.
40.20	Apportioned distance. Set an iron post, 3 ft. long, 1 ins. diam., 26 ins. in the ground for $\frac{1}{4}$ cor. of sec. 30 only, T. 27 S., R 3 W., with brass cap mkd.
	$\frac{1}{4}$  S30 1917
	from which
	A Fir, 12 ins. diam., bears S.33*45'E., 43 lks. dist. mkd. $\frac{1}{4}$ S 30 B T.
	A Fir, 6 ins. diam., bears N.11*E., 27 lks. dist. mkd. $\frac{1}{4}$ S 30 B T.
	Continue ascending S. slope. This $\frac{1}{4}$ cor. is 250 ft. above the creek.
55.50	Trail bears NE and SW.
66.00	Top of Lane Mountain, bears NE and SW., 490 ft. above $\frac{1}{4}$ cor. Descend N. slope.
80.40	Apportioned distance. Set a granite stone, 14x7x7 ins., 10 ins. in the ground for the cor. of secs. 19 and 30, mkd. with 2 notches on S. and 4 notches on N. edge; from which
	A Fir, 30 ins. diam., bears N.67*E., 9 lks. dist. mkd. T 27 S R 3 W S 19 B T.