

Resurvey of E. Bdy. of T. 27 S. R. 4 W.

CHAINS	
	N.0°12'E., resurveying the line bet. secs. 7 and 12. Descend N. slope through heavy timber and dense undergrowth.
25.20	Spring branch, course NW.
39.00	Wire fence, bears N.80°E., and S.80°W.
40.20	Apportioned distance. Set a granite stone, 15x12x10 ins., 10 ins. in the ground for qr. section corner marked $\frac{1}{4}$ on West face; from which A Fir, 15 ins. diam., bears N.31°E., 69 lks. dist. mkd. $\frac{1}{4}$ S 7 B T. A Fir, 20 ins. diam., bears S.37°W., 86 lks. dist. mkd. $\frac{1}{4}$ S 12 B T.
	This cor. is 770 ft. below the sec. cor.; continue down N. slope.
50.00	Leave heavy timber, bears E. and W., and enter scattering timber.
52.00	Draw, course NW., 130 ft. below the $\frac{1}{4}$ sec. cor.; ascend SW. slope.
55.00	Spur, slopes W., 160 ft. above draw; descend NW. slope.
80.40	Apportioned distance. Set a Sandstone, 16x10x4 ins., 11 ins. in the ground, for the corner of sections 1, 6, 7 and 12 marked with 5 notches on South, and 1 notch on North edge, from which A Fir, 16 ins. diam., bears N.60°E., 94 lks. dist. mkd. T 27 S R 3 W S 6 B T. A Fir, 30 ins. diam., bears S.68°15'E., 72 lks. dist. mkd. T 27 S R 3 W S 7 B T.