

Retracement and Resurvey of Subdivisions, T. 27 S., R. 4 W.

CHAINS

Land, mountainous

Soil, 3rd rate

Timber, fir, cedar and hemlock

Undergrowth, maple, fir, cedar and salal-berry

N.0*5'E., resurveying the E. bdy. of sec. 23

Descend NW. slope through heavy timber and dense undergrowth.

15.30 Creek, 4 lks. wide, course NW., 275 ft. below sec. cor.;
thence along W. slope

29.00 Old, deserted cabin, bears E., 180 lks. dist.

38.00 Spur, slopes NW., 40 ft. below creek; descend N. slope

39.26 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ cor. of sec. 24 only with brass cap marked
$$\begin{array}{c} \frac{1}{4} \\ | \\ S24 \\ 1917 \end{array}$$

from which

A fir, 40 ins. diam., bears N.67*E., 55 lks. dist.

Marked $\frac{1}{4}$ S 24 B T

A fir, 40 ins. diam., bears S.73*E., 33 lks. dist.

Marked $\frac{1}{4}$ S 24 B T

This cor. is 90 ft. below the spur

40.37 Apportioned distance

Set a limestone, 14x9x5 ins., 10 ins. in the ground, for
 $\frac{1}{4}$ cor. of sec. 23 only, marked $\frac{1}{4}$ on W. face, from which

A fir, 30 ins. diam., bears S.60*W., 16 lks. dist.

Marked $\frac{1}{4}$ S 23 B T

A fir, 36 ins. diam., bears N.71*W., 60 lks. dist.

Marked $\frac{1}{4}$ S 23 B T

Descend abrupt N. slope

48.00 Head of draw, course W., 200 ft. below $\frac{1}{4}$ cor.

Ascend SW. slope

53.00 Top of spur, slopes W., 100 ft. above draw; descend NE
slope