

Retracement and Resurvey of Subdivisions, T. 27 S., R. 4 W.

CHAINS	
56.50	Head of draw, course W., 110 ft. below spur; ascend SW. slope
77.00	Top of ridge, bears NW. and SE., 290 ft. above draw. Descend NE. slope
79.26	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13 and 24, with brass cap marked <div style="text-align: center; border: 1px solid black; padding: 2px;"> T27S S13 <hr style="width: 50%; margin: 0 auto;"/> S24 R4W 1917 </div> from which A hemlock, 12 ins. diam., bears N.71*E., 142 lks. dist. Marked T 27 S R 4 W S 13 B T A fir, 34 ins. diam., bears S.63*E., 34 lks. dist. Marked T 27 S R 4 W S 24 B T This cor. is 50 ft. below the ridge
80.74	Intersect the point for old cor. of secs. 13, 14, 23 and 24, located by reference to the bearing trees At the exact cor. point, Set a basalt stone, 16x7x4 ins., 11 ins. in the ground for cor. of secs. 14 & 23, marked with 3 notches on N. and S. edges; from which A fir, 32 ins. diam., bears S.60*W., 25 lks. dist. Marked T 27 S R 4 W S 23 B T (Orig. B.T.) A fir, 36 ins. diam., bears N.51*W., 12 lks. dist. Marked T 27 S R 4 W S 14 B T (Orig. B.T.) Land, mountainous Soil, 3rd rate Timber, fir, cedar and hemlock Undergrowth, maple, chinquapin, laurel and fir

Returning to the cor. of secs. 23 & 26
 S.89*36'W., resurveying the line bet. secs. 23 and 26
 Descend NW. slope