

Retracement and Resurvey of Subdivisions, T. 27 S., R. 4 W.

CHAINS	
	Returning to the cor. of secs. 14 & 23
	N.1*20'W., resurveying the E. bdy. of Sec. 14.
	Along E. slope, through heavy timber and dense undergrowth
3.00	Top of spur, slopes NE., 30 ft. above the sec. cor. Descend abrupt N. slope
17.30	North fork of Deer Creek, 5 lks. wide, course NW., 510 ft. below the top of spur
17.70	Wagon road, bears E. and W.; ascend SW. slope
32.00	Spur, slopes W., 280 ft. above the creek Along W. slope
38.53	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 13 only, with brass cap marked <div style="text-align: center;"> $\frac{1}{4}$ S13 1917 </div> from which A W oak, 10 ins. diam., bears N.68*E., 68 lks. dist. Marked $\frac{1}{4}$ S 13 B T A fir, 9 ins. diam., bears S.78*30'E., 181 lks. dist. Marked $\frac{1}{4}$ S 13 B T
39.75	Apportioned distance Set a basalt stone, 14x7x5 ins., 10 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 14 only, marked $\frac{1}{4}$ on W. face, from which A B oak, 20 ins. diam., bears S.75*30'W., 124 lks. dist. Marked $\frac{1}{4}$ S 14 B T A fir, 28 ins. diam., bears N.7*30'W., 227 lks. dist. Marked $\frac{1}{4}$ S 14 B T
42.00	Top of spur, slopes NW., 20 ft. above $\frac{1}{4}$ cor. Descend NW slope
58.70	Draw (dry) course NW., 320 ft. below spur. Along W. slope
79.50	Intersect the cor. of secs. 11, 12, 13 and 14, which is an old, decayed post, marked and witnessed as described