

Retracement and Resurvey of Subdivisions, T. 27 S., R. 4 W.

CHAINS

by the Surveyor General

Alongside the old corner,

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, with brass cap marked

T27SR4W	
S11	S12
S14	S13
1917	

from which

A B oak, 15 ins. diam., bears N.47*E., 82 lks. dist.

Marked T 27 S R 4 W S 12 B T (Orig. B.T.)

A fir, 16 ins. diam., bears S.65*E., 442 lks. dist.

Marked T 27 S R 4 W S 13 B T (New B.T.)

A B oak, 16 ins. diam., bears N.81*W., 14 lks. dist.

Marked T 27 S R 4 W S 11 B T. (Orig. B.T.)

No other tree available; raise a mound of stone,
2 ft. base, 1½ ft. high, W. of cor.

This cor. is 100 ft. above the draw.

Land, mountainous

Soil, 2nd and 3rd rate

Timber, fir, cedar, hemlock, oak and laurel

Undergrowth, maple, fir, cedar and scrub oak

East, retracing the line bet. secs. 12 and 13; at 39.97½ chs. after careful and diligent search, am unable to find any trace of the old ¼ sec. cor., set temp. cor. and at 79.38 chs. fall 180 lks. N. of reestablished cor. of secs. 7, 12, 13 and 18.

Thence

N.88*42'W., resurveying line, bet. secs. 12 and 13.

Ascend NE. slope, through heavy timber and dense undergrowth.

8.50 Top of spur, slopes N., 80 ft. above sec. cor.; descend
NW. slope

29.70 Trail, bears NE. and SW.

30.40 Creek, 2 lks. wide, course N., 530 ft. below spur
Ascend NE. slope