

Retracement and Resurvey of Subdivisions, T. 27 S., R. 4 W.

CHAINS 39.70	Apportioned distance  Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked  $\frac{1}{4} \frac{S12}{S13}$ 1917  from which  A fir, 30 ins. diam., bears N.58°E., 54 lks. dist. Marked $\frac{1}{4}$ S 12 B T  A fir, 10 ins. diam., bears S.16°15'E., 30 lks. dist. Marked $\frac{1}{4}$ S 13 B T  This cor. is 130 ft. above the creek.
42.00	Top of spur, slopes N., 50 ft. above $\frac{1}{4}$ sec. cor. Descend NW. slope
54.00	Creek, 1 lk. wide, course NW., 270 ft. below spur Ascend NE. slope
68.00	Top of spur, slopes N., 320 ft. above the creek Descend NW. slope
79.40	Intersect the cor. of secs. 11, 12, 13 and 14, 190 ft. below the spur.  Land, mountainous Soil, 3rd rate Timber, fir and cedar. Undergrowth, maple, fir, cedar, scrub oak, laurel and salal-berry.

Subdivisions of T. 27 S., R. 4 W.

40.00	I commence at the cor. of secs. 24 and 25, and run East, on a true line, bet. secs. 24 and 25. Ascend NW. slope, through heavy timber and dense undergrowth.  Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked  $\frac{1}{4} \frac{S24}{S25}$ 1917  from which
-------	---