

Subdivisions of T. 27 S., R. 4 W.

CHAINS	
20.85	Trail, bears N. and S.
22.00	Top of spur, slopes N., 190 ft. above the creek; thence along N. slope
24.70	Creek, 1 lk. wide, course NW.; ascend W. slope
33.00	Top of spur, slopes NW., 285 ft. above the creek.
33.20	Mrs. J. Cockelreas' house, bears N.37*E. Descend NE. slope
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S13 $\frac{1}{4}$ S24 1917
	from which
	A hemlock, 10 ins. diam., bears N.50*W., 36 lks. dist. Marked $\frac{1}{4}$ S 13 B T
	A cedar, 17 ins. diam., bears S.70*W., 46 lks. dist. Marked $\frac{1}{4}$ S 24 B T
	This cor. is 150 ft. below the top of the spur; from this cor., Mrs. J. Cockelreas' house bears N.7*E. Thence along broken N. slope
46.70	Spring branch, course N.
50.15	Trail, bears NW. and SE.
53.60	Creek, 4 lks. wide, course NW.; ascend W. slope
63.50	Top of spur, slopes NW., 300 ft. above the creek; ascend along N. slope
76.79	Intersect W. bdy. of T. 27 S., R. 3 W., N.0*12'E., 1.32 chs. from the cor. of secs. 18 and 19 At the point of intersection Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 13 and 24, with brass cap marked

T27S
 R4W | R3W
 CC S13 | S18
 S24 |
 1917