

West Boundary of T. 27 S., R. 5 W.,
 as surveyed by Robert Elder and Henry S. Gile, Deputy Surveyors,
 under their Contract No. 31, dated April 7, 1853.

CHAINS

South, on West Boundary of Secs. 6, 7, 18, 19, 30 and 31.
 Set temp. $\frac{1}{2}$ Sec. posts and at 6 miles I chain and 59 lks.
 Intersect the 6 Standard Parallel 926 lks. West of
 post - therefore the correction will be 1 chain and
 59 lks. South.

June 22, 1853.

True Western Boundary

North, on West boundary of Section 31.

Va. 18°20'E.

Set post cor. to Secs. 31 and 31, from which

A W. Oak, 20 ins. diam., bears N. 22 $\frac{1}{2}$ °E., 441 lks.
 dist.

A W. Oak, 20 ins. diam., bears N. 50 $\frac{1}{2}$ °W., 352 lks.
 dist.

14.59 Road to mine, course N. 20°E and S. 20°W

28.50 Top of hill.

Va. 19°00'E.

+100

40.00 Set $\frac{1}{2}$ Sec. post, from which

-250

A G. Oak, 16 ins. diam., bears S. 43 $\frac{1}{2}$ °E., 90 lks.
 dist.

A G. Oak, 28 ins. diam., bears S. 57°W., 173 lks.
 dist.

60.00 Va. 16°45'E.

80.00 Set post cor. to Secs. 31, 36, 25 and 30, from which

-50

A W. Oak, 26 ins. diam., bears S. 29°W., 182 lks.
 dist.

A W. Oak, 16 ins. diam., bears S. 13 $\frac{1}{2}$ °E., 287 lks.
 dist.

A W. Oak, 22 ins. diam., bears N. 40 $\frac{1}{2}$ °E., 150 lks.
 dist.

A G. Oak, 9 ins. diam., bears N. 32 $\frac{1}{2}$ °W., 188 lks.
 dist.

South 28 chs. ascending South slope of hill - balance
 descend North on East slope of hill - all timbered
 with scattering Oak.