Insert page follows 1119
page ~~5108~~ 5108

Sixth Standard Parallel South,
(North Bdy. of T. 28 S., R. 5 W.)

Chains		
	West, on North Bdy. of Sec. 4	
80.00	Set post cor. to Secs. 4 and 5, from which	
	A Fir, 16 ins. diam., bears S.82½°W., 54 lks.	
	A Fir, 14 ins. diam., bears S.47½°E., 70 lks.	
	West, on North Bdy. of Sec. 5.	
	Var. 19°20'E.	
10.00	Top of spur, course North and South.	+300
12.44	A Fir, 16 ins. dia.	-40
24.00	A Stream, 6 lks. wide, course North.	-400
40.00	Set qr. sec. post, from which	+400
	A Y. Oak, 6 ins. diam., bears S.52°E., 124 lks.	
	A Y. Oak, 16 ins. diam., bears S.13½°W., 108 lks.	
	Var. 18°15'E.	
65.50	Top of ridge, course N and S.	+500
80.00	Set post cor. to Secs. 5 and 6, from which	-450
	A Fir, 16 ins. diam., bears S.1°W., 16 lks.	
	A Fir, 16 ins. diam., bears S.65½°E., 56 lks.	
	A portion of South Bdy. T. 27 S., R. 5 W.	
	West, on South bdy. of Sec. 33 ----------	
80.00	Cor. to Secs. 32 and 33, from which	
	A Fir, 14 ins. diam., bears N.16°W., 18 lks.	
	A Fir, 12 ins. diam., bears N.42°E., 8 lks.	
	West, on South Bdy. of Sec. 32.	
	Var. 19°35'E.	
9.00	Top of spur, course N. and S.	
11.25	A Fir, 15 ins. dia.	
22.60	A Stream, 4 lks. wide, course North.	
32.50	Leave brushy fir timber and enter oak openings, course nearly N. and S.	
38.83	To Standard qr. sec. cor.	

over

U. S. GOVERNMENT PRINTING OFFICE: 1891 6—8155