

## SUBDIVISIONS, T. 27 S., R. 5 W.

CHAINS		
42.00	Begin to ascend hill N.20°E and S.20°W.	+10
51.50	Top of hill, N.20°E and S.20°W.	+250
63.00	Foot of hill.	-450
68.00	Begin to ascend hill NE and SW.	
79.62	To Section corner.	+450
	Land, all hilly Oak openings.	
	Soil, 2nd rate.	
<hr/>		
	N.9°W Between Secs. 10 and 11.	
		Va. 18°35'E.
24.00	Top of hill, course NE and SW.	+500
40.00	Set $\frac{1}{4}$ Sec. post, from which	-200
	A Y. Oak, 10 ins. diam., bears N.27°W., 33 lks. dist.	
	A Y. Oak, 11 ins. diam., bears S.59°E., 35 lks. dist.	
		Va. 19°30'E.
63.00	Begin to descend steep hill NE and SW.	+150
80.00	Set post corner to Secs. 2, 3, 10 and 11, from which	-400
	A W. Oak, 7 ins. diam., bears N.41°E., 78 lks. dist.	
	A Y. Oak, 14 ins. diam., bears N.38 $\frac{1}{2}$ °W., 60 lks. dist.	
	A W. Oak, 6 ins. diam., bears S.82°W., 49 lks. dist.	
	A Y. Oak, 11 ins. diam., bears S.35°E., 137 lks. dist.	
	Land, all hilly Oak openings.	
	Soil, 2nd and 3rd rate.	
<hr/>		
	N.89°59'E. On Random line between Secs. 2 and 11.	
		Va. 28°10'E.
79.30	Intersect. N and S line 1 lk. S of Sec. corner.	
	S.89°59'W On true line between Secs. 2 and 11.	