

- 4 -
County Surveyor's Record, Douglas County, Oregon

Exterior Lines of T. 28 S., R. 7 W.

CHAINS

A Red Fir, 15 ins. diam., bears N.50*E., 56 lks.
dist.

A Laurel, 4 ins. diam., bears N.45*W., 5 lks. dist.

For closing cor.

40.00 Set $\frac{1}{4}$ Sec. post, from which +30

A B. Oak, 10 ins. diam., bears N.10*W., 43 lks.
dist.

A W. Oak, 15 ins. diam., bears S.33*W., 82 lks.
dist.

47.40 Set $\frac{1}{4}$ Sec. post, from which -10

A W. Oak, 10 ins. diam., bears N.31*W., 11 lks.
dist.

A B. Oak, 12 ins. diam., bears S.22*E., 48 lks.
dist.

63.20 A small stream 6 lks. wide, course N.27*W.

80.00 Set a post, cor. of Secs. 1 and 6, from which

A B. Oak, 8 ins. diam., bears S.15*E., 150 lks.
dist.

A. B. Oak, 8 ins. diam., bears S.35*W., 130 lks.
dist.

Soil, second rate.

Land, rolling.

Timber, Oak openings.

This corner is some 10.00 chains S.45*E. of the Coast Range of mountains, a cliff 800 ft. high, course N.38*E. and S.45*W. The 6th Standard parallel strikes the Coast Range of mountains near the new trail, from Umpqua Valley to Coos Bay.

Exterior Lines of Tp. 27 S., R. 7 W.
as surveyed by Dennis Hathorn, Deputy Surveyor,
under Contract No. 57, dated April 12, 1855.