

County Surveyor's Record, Douglas County, Oregon

5277

X

Retracement of the 6th. Standard Parallel South, through R. 8 W. as surveyed by William P. Hayden, Deputy Surveyor under contract No. 656 dated May 21, 1896.

CHAINS

I now begin at the established SE. cor. of T 27 S R 8 W. Willamette Meridian Oregon. Latitude 43°10'N. Longitude 123°35'W. (Supplied) which cor. I restore from the original witness trees still standing to wit:
 A black oak, 15 ins. diam., bears N.67°E., 56 lks. dist., marked T 27 S R 7 W S 31 B T.

A white oak, 18 ins. diam. (now dead) bears N.40°W., 129 lks. dist., marked T 27 S R 8 W S 36 B T.

By setting a post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for standard cor. of Tp. 27 S Rs 7 and 8 W marked S C T 27 S on N., R 7 W S 31 on E. R 8 W S 36 on W. faces, with 6 grooves on N.E. & W. faces, from which the original witness trees above described bear as heretofore recited and agreeing with description furnished by the Surveyor General, except the black oak, which is now 24 ins. diam. The marking upon it is plainly visible after removing the new growth of wood. The marking on the white oak, is plainly visible. These trees were marked 41 years ago. This cor. is 8.99 chs. W. from the Standard NE. cor. of T 28 S R 8 W.

From the Standard cor. of T 27 S Rs 7 and 8 W. I run West on the S. bdy. of sec. 36. to retrace the 6th Standard Parallel South and set cors. for T 27 S R 8 W.

Va.20°15'E.

Toward Coast Range Mountains.

31.00 S C ¼ Sec. Cor. Sec. 1. by both sets of chainmen (original position of post established from witness trees as described by Surveyor General.)

40.00 By both sets of chainmen. Set a white oak post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for ¼ sec. cor. marked S C ¼ S. on N. face, from which
 A black oak, 10 ins. diam., bears N.42°30'W., 110 lks. dist., marked ¼ S B T.

See corrective notes to follow

See corrective notes to follow