

Retracement of the 6th Standard Parallel South, through R. 8 W.

CHAINS

Mountainous land, or land covered with dense undergrowth, 80.00 chs.

No latitude taken today on account of the sky being overcast.

July 22, 1896.

July 23, 1896

W. on S. bdy. of sec. 32.

Ascend from cor.

- 5.00 Top of ascent, 300 ft. above Wilson Creek, over level ground through heavy timber.
- 34.87 Stream 2 lks. wide, course N.
- 34.94 $\frac{1}{2}$ sec. cor. post on N. side of sec. 5.
Difference bet. measurements of 40.00 chs. by two sets of chainmen is 8 lks. By 1st set 39.96 chs. by 2nd set 40.04 chs. the mean of which is
- 40.00 Set a yew post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for Standard $\frac{1}{2}$ Sec. Cor: marked S C $\frac{1}{2}$ ^S on N face, from which
A cedar, 14 ins. diam., bears N.40*E., 36 lks. dist., marked S C $\frac{1}{2}$ S B T.
A cedar, 40 ins. diam., bears N.8*W., 33 lks. dist., marked S C $\frac{1}{2}$ S B T.
- 74.50 S.C. to Secs. 5 and 6. Post lying on ground. Witness trees as described by the Surveyor General.
Difference bet. measurements of 80.00 chs. by two sets of chainmen is 10 lks. By 1st set 79.95 chs. by 2nd set 80.05 chs. the mean of which is
- 80.00 Set a yew post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for Standard Cor: to Secs. 32 and 31 marked S C T 27 S R 8 W on N, S 31 on W, and S 32 on E faces, with 1 groove on W. and 5 grooves on E. faces; from which
A fir, 30 ins. diam., bears N.54*E., 50 lks. dist., marked T 27 S R 8 W S 32 B T.