

## County Surveyor's Record, Douglas County, Oregon

## Willamette Meridian through T. 28 S.

CHAINS

30.20

Intersect 6th. Standard Parallel, 1.85 chs. E. of cor.  
to T 27 S R 1 E and 1 W.

Set a basalt stone 15x10x8 ins., 10 ins. in ground for  
closing cor. of T 28 S R 1 W marked C C. on N. and  
with 6 notches on S. and E. edges from which,

A fir, 18 ins. diam., bears S.80\*W., 24 lks. dist.,  
marked T 28 S R 1 W S 1 B T.

A fir, 12 ins. diam., bears S.45\*E., 100 lks. dist.,  
marked T 28 S R 1 W S 6 B T.

Land, mountainous.

Soil, stony, and 3rd. rate.

Timber, fir, pine and hemlock.

Undergrowth, laurel.

Mountainous or heavily timbered land 30.20 chs.

No difference between measurement of 30.20 chs. by two  
sets of chainmen.

South Boundary of T. 28 S., R. 1 W.  
Same Deputy and Contract.

I begin at the cor. of T. 28 and 29 S., R. 1 W. which I  
established. June 28 1902.

Thence I run.

West, bet. secs. 1 and 36.

Over level land through heavy timber and dense under-  
growth.

16.75 Eber Wright's cabin bears N. 1.00 chs. dist.,

20.25 A creek, 25 lks. wide course S.

Ascend.

38.25 Top of ridge point; descend bears N. and S.

40.00 Set a basalt stone, 14x12x5 ins., 10 ins., in ground

for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on N. face; from which,

A fir, 36 ins. diam., bears S.50\*E., 55 lks. dist.,  
marked  $\frac{1}{4}$  S 1 B T.