

County Surveyor's Record, Douglas County, Oregon

West boundary of T. 28 S., R. 1 W., Same deputy and contract

CHAINS

cor. of secs. 7, 12, 13 and 18, marked with 4 notches on S. and 2 notches on N. edges; from which,

A pine, 12 ins. diam., bears N.38*E., 37 lks. dist., marked T 28 S R 1 W S 7 B T.

A pine, 12 ins. diam., bears S.32*E., 60 lks. dist., marked T 28 S R 1 W S 18 B T.

A fir, 24 ins. diam., bears S.10*W., 65 lks. dist., marked T 28 S R 2 W S 13 B T.

A fir, 24 ins. diam., bears N.15*W., 59 lks. dist., marked T 28 S R 2 W S 12 B T.

Land mountainous.

Soil, 4th. rate.

Timber, fir, hemlock, pine, cedar, laurel.

Undergrowth, laurel and vine maple.

Mountainous or heavily timbered land or land covered with dense undergrowth. 80.00 chs.

North, bet. secs. 7 and 12.

Along west, slope through heavy timber and dense undergrowth.

17.75 A spring branch, 1 lk. wide, course, W.

40.00 Set a basalt stone, 15x12x8 ins., 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W. face; from which,

A hemlock, 12 ins. diam., bears N.35*E., 34 lks. dist., marked 1/4 S 7 B T.

A hemlock, 18 ins. diam., bears West, 20 lks. dist., marked 1/4 S. 12 B T.

42.00 Top of divide 1000 ft. high, bears SE. and NW.

Thence along divide.

72.75 A spring branch 2 lks. wide, course. SE.

80.00 Set a basalt stone, 12x10x8 ins. 8 ins. in ground for cor of sec. 1, 6, 7 and 12, marked with 5 notches on S. and 1 notch on N. edges; from which,

A fir, 14 ins. diam., bears N.50*E., 45 lks. dist., marked T 28 S R 1 W S 6 B T.