

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 28 S. R. 1 W. Same Deputy and Contract

CHAINS	
80.00	Intersect will Mer. 10 lks N. of the cor. of secs. 25 and 36, which I established June 28, 1902.
	Thence I run.
	N.89*56'W., on a true line bet. secs. 25 and 36.
	Descend through heavy timber and dense undergrowth.
1.50	James Oscar Nimland's cabin bears S. 1.00 ch. dist.,
2.50	A spring Branch 5 lks. wide, course S.
	Ascend, bears N. and S.
27.25	Top of ridge, bears SE. and NW.
	Descend.
40.00	Set a basalt stone, 15x14x12 ins, 10 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face; from which,
	A fir, 14 ins. diam., bears S.20*E., 40 lks. dist., marked $\frac{1}{4}$ S 36 B T.
	A fir, 36 ins. diam., bears N.71*W., 54 lks. dist., marked $\frac{1}{4}$ S 25 B T.
55.00	Foot of descent.
	Dry run, course S.
	Ascend.
63.25	Top of spur, bears N. & S.
	Descend.
80.00	The cor. of secs. 25, 26, 35 and 36.
	Land, mountainous.
	Soil, stony, 4th. rate.
	Timber, fir, hemlock, cedar and laurel.
	Undergrowth, laurel and huckleberry.
	Mountainous, or heavily timbered land or land covered with dense undergrowth, 80.00 chs.
	N.0*1'W. bet. secs. 25 and 26.
	Ascend through heavy timber and dense undergrowth.
20.00	Top of divide, bears S.20*E., N.20*W., descend.
40.00	Set a basalt stone, 12x8x8 ins., 8 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face; from which,
	A fir, 18 ins. diam., bears N.40*E., 32 lks. dist., marked $\frac{1}{4}$ S. 25 B T.