

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 28 S. R. 1 W.

CHAINS	
	<p>marked <math>\frac{1}{4}</math> S 25 B T.</p> <p>A fir, 14 ins. diam., bears N.52*W., 55 lks. dist.,</p> <p>marked <math>\frac{1}{4}</math> S 24 B T.</p>
56.25	<p>Foot of descent.</p> <p>A spring branch 5 lks. wide, course, SW.</p> <p>Ascend.</p>
79.86	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land Mountainous.</p> <p>Soil, 4th. rate.</p> <p>Timber, fir, hemlock, pine, cedar and laurel.</p> <p>Undergrowth, laurel and vine maple.</p> <p>Mountainous or heavily timbered land or land covered with dense undergrowth. 79.86 chs.</p> <p>August 11, 1902.</p>
	<p>At the cor. of secs. 23, 24, 25 and 26.</p> <p>Thence I run.</p> <p>N.0*01'W. bet. secs. 23 and 24.</p> <p>Ascend through heavy timber and dense undergrowth, bears NE and SW.</p>
10.00	<p>Bearing of hill changes to N. and S.</p>
40.00	<p>Set a basalt stone, 15x12x10 ins. 10 ins, in ground for <math>\frac{1}{4}</math> sec. cor. marked <math>\frac{1}{4}</math> on W. face; from which,</p> <p>A fir, 24 ins. diam., bears SE. 29 lks. dist.,</p> <p>marked <math>\frac{1}{4}</math> S 24 B T.</p> <p>A fir, 14 ins. diam., bears SW. 36 lks. dist.,</p> <p>marked <math>\frac{1}{4}</math> S 23 B T.</p>
80.00	<p>Set a basalt stone, 15x12x5 ins. 10 ins., in the ground for cor. of sec. 13, 14, 23 and 24 marked with 3 notches on S. and 1 notch on E. edges; from which,</p> <p>A fir, 24 ins. diam., bears N.66*E., 65 lks. dist.,</p> <p>marked T 28 S R 1 W S 13 B T.</p> <p>A fir, 40 ins. diam., bears S.65*E., 23 lks. dist.,</p> <p>marked T 28 S R 1 W S 24 B T.</p>