

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 28 S., R. 1 W.

CHAINS

A fir, 16 ins. diam., bears S.61\*W., 68 lks. dist.,  
marked T 28 S R 1 W S 2 B T.

Land, mountainous.

Soil, stony, 4th. rate.

Timber, fir, hemlock, pine, laurel and cedar.

Undergrowth, laurel and vine maple.

Mountainous or heavily timbered land or land covered  
with dense undergrowth. 29.90 chs.

August 13, 1902

At the cor. of secs. 2, 3, 35 and 36 in the S. Edy.

Thence I run.

N.0\*2'W. bet. secs. 34 and 35 along side of mountain,  
bears, N. and S. through heavy timber and dense  
Undergrowth.

18.50 Top of ridge, bears E. and W.

Descend.

40.00 Set a basalt stone, 15x10x6 ins., 10 ins. in ground for

$\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on W. face; from which,

A fir, 10 ins. diam., bears N.70°E., 17 lks. dist., marked  $\frac{1}{4}$  S. 35 B T. JC DCSO

A fir, 10 ins. diam., bears S.33\*W., 25 lks. dist.,

marked  $\frac{1}{4}$  S. 34 B T.

65.30 A spring branch, 4 lks. wide, course E.

80.00 Set a basalt stone, 15x10x5 ins., 10 ins. in ground for

cor. of secs. 26, 27, 34 and 35 marked with 1 notch

on S. and 2 notches on E. edges; from which,

A fir, 10 ins. diam., bears N.58\*E., 44 lks. dist.,

marked T 28 S R 1 W S 26 B T.

A fir, 20 ins. diam., bears SE., 25 lks. dist.,

marked T 28 S R 1 W S 35 B T.

A hemlock, 14 ins. diam., bears S.24 $\frac{1}{2}$ \*W., 44 lks.

dist., marked T 28 S R 1 W S 34 B T.

A hemlock, 14 ins. diam., bears N.62\*W., 44 lks. dist.

marked T 28 S R 1 W S 27 B T.

Land, mountainous.

Soil, 4th, rate.

\* Added 3/17/2010