

## County Surveyor's Record, Douglas County, Oregon

## Subdivision of T. 28 S., R. 1 W.

CHAINS	
	Ascend.
80.00	<p>Set a basalt stone, 12x10x8 ins. 8 ins. in ground for cor. of secs. 14, 15, 22, and 23, marked with 3 notches on S. and 2 notches on E. edges; from which,</p> <p>A pine, 14 ins. diam., bears N.41*E., 41 lks. dist., marked T 28 S R 1 W S 14 B T.</p> <p>A pine, 10 ins. diam., bears S.35*E., 16 lks. dist., marked T 28 S R 1 W S 23 B T.</p> <p>A fir, 10 ins. diam., bears S.69*W., 33 lks. dist., marked T 28 S R 1 W S 22 B T.</p> <p>A fir, 10 ins. diam., bears N.84*W., 40 lks. dist., marked T 28 S R 1 W S 15 B T.</p>
	Land, mountainous.
	Soil, 4th. rate.
	Timber, fir, hemlock, pine, cedar and laurel.
	Undergrowth, laurel and vine maple.
	Mountainous or heavily timbered land or land covered
	with dense undergrowth, 80.00 chs.
	N.89*53'E. on a random line bet secs. 14 and 23.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line 20 lks. N. of the cor. of secs.
	13, 14, 23 and 24.
	Thence I run.
	N.89*58'W. on a true line bet secs. 14 and 23.
	Over divide, bears N. and S. through heavy timber and
	dense undergrowth.
4.00	Descend.
36.00	Foot of descend.
	Ascend.
40.00	Set a basalt stone, 12x10x10 ins., 8 ins. in ground for
	$\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face; from which,
	A fir, 16 ins. diam., bears SE. 68 lks. dist.,
	marked $\frac{1}{4}$ S 23 B T.