

## County Surveyor's Record, Douglas County, Oregon

## Subdivision of T. 28 S., R. 1 W.

CHAINS	
	<p><math>\frac{1}{4}</math> sec. cor. marked <math>\frac{1}{4}</math> on N. face; from which,</p> <p>A fir, 10 ins. diam., bears S.6 *E., 12 lks. dist., marked <math>\frac{1}{4}</math> S 22 B T.</p> <p>A fir, 16 ins. diam., bears NW. 20 lks. dist., marked <math>\frac{1}{4}</math> S 15 B T.</p>
60.00	<p>Foot of descent.</p> <p>A spring branch, 5 lks. wide, course S.</p> <p>Ascend.</p>
80.20	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, mountainous.</p> <p>Soil, 4th. rate.</p> <p>Timber, fir, hemlock, pine, cedar, and laurel.</p> <p>Undergrowth, laurel and huckleberry.</p> <p>Mountainous or heavily timbered land or land covered with dense undergrowth. 80.20 chs.</p>
	<p>N.0*2'W., bet. secs. 15 and 16.</p> <p>Ascend, over stony ground, through scattered timber and dense undergrowth.</p>
15.50	Top of spur, bears E. and W.
16.00	Bearing of mountain changes to N. and S.
35.00	Top of divide, bears E. and W.
	Descend.
39.00	C. M. Rinker's cabin bears W. 1.00 chs.
40.00	<p>Set a basalt stone, 15x10x6 ins., 10 ins. in ground for</p> <p><math>\frac{1}{4}</math> sec. cor., marked <math>\frac{1}{4}</math> on W. face; from which,</p> <p>A fir, 10 ins. diam., bears S.81*E., 9 lks. dist., marked <math>\frac{1}{4}</math> S 15 B T.</p> <p>A fir, 14 ins. diam., bears N.55*W., 62 lks. dist., marked <math>\frac{1}{4}</math> S 16 B T.</p>
72.75	A spring branch, 5 lks. wide, course, NE.
78.75	Walter'Boon's cabin bears W. 1.00 chs.
80.00	<p>Set a basalt stone 15x10x6 ins., 10 ins. in ground for</p> <p>cor. of secs. 9, 10, 15, and 16, marked with 4 notches on S. and 3 notches on E. edges; from which,</p>