

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 28 S., R. 1 W.

CHAINS

undergrowth.

- 2.50 A spring branch, 10 lks. wide, course N.75°E.
 26.25 A creek, 15 lks. wide, course E.
 29.15 Intersect 6th. standard Parallel South, 65 lks. E. of
 the standard cor. of secs. 33., and 34.

Set a basalt stone, 12x8x8 ins., 8 ins. in ground for
 closing cor. of secs. 3 and 4, marked C. C. on South
 and 3 notches on E. and W. edges; from which,

A fir, 10 ins. diam., bears S.60°E., 18 lks. dist.,
 marked T 28 S R 1 W S 3 B T.

A cedar, 12 ins. diam., bears S.12°W., 32 lks.
 dist., marked T 28 S R 1 W S 4 B T.

Land, Mountainous.

Soil, 3rd. rate.

Timber, fir, hemlock, cedar, pine and laurel.

Undergrowth, laurel and willow.

Mountainous or heavily timbered land or land covered
 with dense undergrowth, 29,15 chs.

August 20, 1902

At the cor. of secs. 32 and 33 on the S. Bdy. which I
 established August 5, 1902.

Thence I run.

N.0°3'W., bet. secs. 32 and 33.

Descend through heavy timber and dense undergrowth, bears
 E. and W.

- 40.00 Set a hemlock post, 3½ ft. long, 3 ins. sq. 24 ins. in
 the ground for ¼ sec. cor. marked ¼ S. 32 on W. and
 33 on E. face; from which,

A laurel, 10 ins. diam., bears N.12°E., 36 lks.
 dist., marked ¼ S 33 B T.

A fir, 14 ins. diam., bears N.55°W., 11 lks. dist.,
 marked ¼ S 32 B T.