

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 28 S., R. 1 W.

CHAINS	
	West on a random line, bet. secs. 19 and 30.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
76.80	Intersect W. bdy. of T. at the cor. of secs. 19, 24, 25 and 30.
	Thence I run.
	East on a true line bet. secs. 19 and 30.
	Over rolling land through heavy timber and dense under- growth.
3.00	A spring branch, 1 lk. wide, course S.
6.00	A spring branch, 5 lks. wide, course S.25*E.
31.50	A spring branch, 10 lks. wide, course S.25*E.
	Ascent, bears SE and NW.
36.80	Set a basalt stone, 15x12x8 ins., 10 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face; from which, A pine, 24 ins. diam., bears S.65*E., 45 lks. dist., marked $\frac{1}{4}$ S 30 B T. A fir, 30 ins. diam., bears N.30*W., 28 lks. dist., marked $\frac{1}{4}$ S 19 B T.
60.00	Descend, bears N. and S.
76.80	The cor. of secs. 19, 20, 29 and 30.
	Land, mountainous.
	Soil, 4th. rate.
	Timber, fir, hemlock, pine, cedar and laurel.
	Undergrowth, laurel and willow.
	Mountainous or heavily timbered land or land covered with dense undergrowth, 77.80 chs.
	August 26, 1902
	N.0*4'W. bet. secs. 19 and 20.
	Over rolling land through scattering timber and dense undergrowth.
40.00	Set a basalt stone, 12x10x5 ins., 8 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face; from which, A fir, 12 ins. diam., bears N.52*E., 38 lks. dist., marked $\frac{1}{4}$ S 20 B T.