

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 28 S., R. 1 W.

CHAINS	
	A fir, 14 ins. diam., bears N.50*W., 52 lks. dist., marked $\frac{1}{4}$ S 19 B T.
77.25	A spring branch, 5 lks. wide, course E.
80.00	Set a basalt stone, 12x10x6 ins., 8 ins. in ground for cor. of secs. 17, 18, 19 and 20. Marked with 3 notches on S. and 5 notches on E. edges; from which, A fir, 12 ins. diam., bears N.75*E., 28 lks. dist., marked T 28 S R 1 W S 17 B T. A fir, 24 ins. diam., bears S.5*E., 28 lks. dist., marked T 28 S R 1 W S 20 B T. A pine, 24 ins. diam., bears S.3*W., 43 lks. dist., marked T 28 S R 1 W S ¹⁹ 79 B T. A pine, 30 ins. diam., bears N.40*W., 54 lks. dist., marked T 28 S R 1 W S 18 B T.
	Land, mountainous.
	Soil, 3rd. rate.
	Timber, fir, pine, hemlock and laurel.
	Undergrowth, laurel.
	Mountainous, or heavily timbered land or land covered with dense undergrowth, 80.00 chs.
	S.89*58'E, on a random line bet. secs. 17 and 20.
40.00	Set temp $\frac{1}{4}$ sec. cor.
80.20	Interest N. and S. line 5 lks. S. of the cor. of secs. 16, 17, 20 and 21. Thence I run. West, on a true line, bet. secs. 17 and 20. Descend through scattering timber and dense undergrowth.
7.00	A spring branch, 2 lks. wide, course S. Ascend.
40.10	Set a basalt stone, 15x10x5 ins., 10 ins., in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face; from which, A pine, 12 ins. diam., bears NE., 72 lks. dist., marked $\frac{1}{4}$ S 17 B T.