

East Boundary of T. 28 S., R. 3 W., W. M.  
 As surveyed by Samuel C. Flint, Deputy Surveyor  
 Under Contract No. 459, dated Aug. 3, 1882

CHAINS

Began at standard cor. of T. 27 S., Rs. 2 and 3 W. which is a post, 4 ins. sq., and marked S C T 27 S on N., R 2 W S 31 on E and R 3 W S 36 on W faces with 6 notches on NE and W faces, from which

A fir, 12 ins. diam., bears N.43\*E., 70 lks. dist.  
 marked T 27 S R 2 W S 31 B T.

A fir, 30 ins. diam., bears N.55\*W., 46 lks. dist.  
 marked T 27 S R 3 W S 36 B T.

A fir, 36 ins. diam., bears S.25\*W., 42 lks. dist.  
 marked T 28 S R 3 W S 1 B T.

Thence I run

South, on true line, bet. secs. 1 and 6.

Va.20\*E.

2.50 Summit of mountain.

5.00 Commenced to descend.

40.00 Set laurel post, 3 ft. long, 3 ins. sq., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked on E and W faces  $\frac{1}{4}$  S. from which

A fir, 12 ins. diam., bears N.80\*W., 21 lks. dist.  
 marked  $\frac{1}{4}$  S B T.

A fir, 36 ins. diam., bears N.65\*E., 51 lks. dist.  
 marked  $\frac{1}{4}$  S B T.

44.50 Spring branch, 2 lks. wide, course W.

68.50 Spring branch, 2 lks. wide, course SW.

80.00 Set cedar post, 4 ft. long, 4 ins. sq., 24 ins. in the ground for cor. to secs. 1, 6, 7 and 12, and marked T 28 S S 6 on NE, R 2 W S 7 on SE, R 3 W S 12 on SW and S 1 on NW faces, with 1 notch on N and 5 notches on S edges, from which

A fir, 24 ins. diam., bears N.25\*E., 39 lks. dist.  
 marked T 28 S R 2 W S 6 B T.

A fir, 20 ins. diam., bears S.55\*E., 20 lks. dist.  
 marked T 28 S R 2 W S 7 B T.