

## County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 28 S., R. 3 W., W. M.

CHAINS

A cedar, 20 ins. diam., bears N.30\*W., 8 lks.  
dist. marked T 28 S R 3 W S 13 B T.

This mile is high, rocky and mountainous, mostly burnt ridges.

Soil, 4th rate.

Densely covered with forests of burnt timber and thick burnt undergrowth of vine maple, huckleberry and hazel.

August 31, 1882.

A Portion of South and West Boundaries of  
T. 28 S., R. 2 W., as surveyed by Wm. N. Gibb,  
under contract No. 783, dated Dec. 3, 1908.

I begin at the cor. secs. 13, 24, 18 and 19, which is a stake marked and witnessed as described by the Surveyor General.

Thence I run

S on W bdy. T. 28 S., R. 2 W.

At 2 miles, 75 chs., and 16 lks., intersect 38.41 chs. due east of cor. T. 29 S., Rs. 2 and 3 W.

Set granite stone, 10x12x16 ins., 11 ins. in the ground for cor. T. 28 S., Rs. 2 and 3 W., marked with 6 notches on N., E and W edges, from which

A laurel, 7 ins. diam., bears N.69\*E., 11 lks.  
dist., marked T 28 S R 2 W S 31 B T.

A fir, 6 ins. diam., bears N.54\*W., 9 lks.  
dist., marked T 28 S R 3 W S 36 B T.

September 3, 1909.

Thence I run

N on true line, bet. secs. 31 and 36, on W bdy. T. 28 S., R. 2 W.

Ascend S. slope of mountain, through dense underbrush