

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 28 S., R. 2 W.

CHAINS

and dig pits, 18x18x12 ins., E and W of cor. and raise mound of earth, 3½ ft. base, 1½ ft. high, N of cor. from which

A cedar, 9 ins. diam., bears N.6°E., 20 lks.

dist., marked ¼ S 31 B T.

No other tree fit to mark.

48.00 Top of spur, bears N and S.; descend SE slope.
 55.72 Stream, 2 lks. wide, flows S.; ascend SW slope.
 72.00 Top of ridge, bears N and S.; descend NE slope.
 74.00 Stream, 2 lks. wide, flows S.; ascend SW slope.
 80.00 Set cedar stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for cor. secs. 31 and 32, marked T 28 S S 32 on NE., and R 2 W S 31 on NW face, with 1 notch on W and 5 notches on E edge, from which

A fir, 12 ins. diam., bears N.50°E., 29 lks.
 dist., marked T 28 S R 2 W S 32 B T.

A cedar, 5 ins. diam., bears N.72°W., 10 lks.
 dist., marked T 28 S R 2 W S 31 B T.

Land, mountainous.
 Soil, rocky; 4th rate.
 Timber, cedar, fir and hemlock.
 Underbrush, young firs and cedars, vine maple, greasewood and willows.
 Land mountainous, covered with dense underbrush or heavily timbered and exceptionally difficult to survey, 80.00 chs.

Thence E on S bdy. sec. 32, through dense underbrush and scattering timber; ascend SW slope.

12.00 Enter heavy timber.
 16.00 Ridge, bears NW and SE.; ascend NW slope.
 38.00 Descend along NE slope.
 40.00 Set yew stake, 3 ft. long, 5 ins. sq., 24 ins. in the