

## Subdivision of T. 28 S., R. 2 W.

## CHAINS

Thence I run

N.2'E., on true line, bet. secs. 20 and 21.

Through dense underbrush and heavy timber; ascend SW slope.

12.00 Top of ridge, bears E and W.; descend NW slope.

20.30 Ravine bears W.; ascend SW slope.

28.00 Top of ridge, bears E and W.; descend NW slope.

31.30 Creek, 3 lks. wide, flows W.; ascend S slope.

34.50 Creek, 10 lks. wide, flows W.; ascend SW slope.

40.00 Set granite stone, 8x12x16 ins., 12 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W face, from which  
 A hemlock, 12 ins. diam., bears S.85\*W., 20 lks. dist., marked  $\frac{1}{4}$  S 20 B T.  
 A fir, 48 ins. diam., bears N.76\*E., 16 lks. dist., marked  $\frac{1}{4}$  S 21 B T.

45.00 Descend NW slope.

60.50 Creek, 1 lk. wide, flows E.

71.00 Branch of Cavite Creek, 15 lks. wide, flows NE.; ascend SE slope.

73.50 Top of cliff, 100 ft. high; descend.

80.00 Set granite stone, 5x12x16 ins., 11 ins. in the ground for cor. secs. 16, 17, 20 and 21, marked with 3 notches on S and 4 notches on E edges, from which  
 A fir, 8 ins. diam., bears N.54\*E., 94 lks. dist., marked T 28 S R 2 W S 16 B T.  
 A fir, 14 ins. diam., bears S.44\*E., 3 lks. dist., marked T 28 S R 2 W S 21 B T.  
 A fir, 10 ins., diam., bears S.17\*45'W., 21 lks. dist., marked T 28 S R 2 W S 20 B T.  
 A hemlock, 8 ins. diam., bears N.46\*W., 45 lks. dist., marked T 28 S R 2 W S 17 B T.

Land, mountainous.

Soil, rocky; 3d rate.