

Subdivision of T. 28 S., R. 2 W.

CHAINS

survey, 80.04 chs.

June 22, 1910.

Thence I run

N.2'E., on true line, bet. secs. 16 and 17; through
dense underbrush and heavy timber.

Ascend SE slope.

18.00 Top of ridge, bears E and W.; descend N slope.

26.00 Stream, 3 lks. wide, flows NE.; ascend SE slope.

40.00 Set granite stone, 5 x8x16 ins., 11 ins. in the
ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from
which

A fir, 30 ins. diam., bears S.55*30'W., 37 lks.
dist., marked $\frac{1}{4}$ S 17 B T.

A fir, 30 ins. diam., bears N.72*30'E., 58 lks.
dist., marked $\frac{1}{4}$ S 16 B T.

64.00 Ridge, bears E and W.; descend NE slope.

80.00 Set yew stake, 3 ft. long, 4 ins. sq., 24 ins. in the
ground for cor. secs. 8, 9, 16 and 17, marked
T 28 S S 9 on NE., R 2 W S 16 on SE., S 17 on SW.,
and S 8 on NW face, with 4 notches on E and 4 notches
on S edge, from which

A fir, 12 ins. diam., bears N.31'E., 53 lks.
dist., marked T 28 S R 2 W S 9 B T.

A fir, 14 ins. diam., bears S.34'E., 40 lks.
dist., marked T 28 S R 2 W S 16 B T.

A fir, 18 ins. diam., bears S.14*W., 20 lks.
dist., marked T 28 S R 2 W S 17 B T.

A fir, 24 ins. diam., bears N.60*W., 37 lks.
dist., marked T 28 S R 2 W S 8 B T.

Land, mountainous.

Soil, rocky; 3d rate.

Timber, cedar, fir, hemlock and matherone.