

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 28 S., R. 2 W.

CHAINS	
10.00	Creek, 4 lks. wide, flows N.
16.00	Top of ridge, bears E and W.; descend NW slope.
30.00	Creek, 2 lks. wide, flows N.; ascend NE slope.
39.93 $\frac{1}{2}$	Set cedar post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 8 on N and 17 on S face, from which A fir, 8 ins. diam., bears S.27*W., 83 lks. dist., marked $\frac{1}{4}$ S 17 B T. A fir, 10 ins. diam., bears N.40*E., 30 lks. dist., marked $\frac{1}{4}$ S 8 B T.
45.00	Top of ridge, bears N and S.; descend NW slope.
58.50	Creek, 2 lks. wide, flows NE.; ascend E slope.
76.00	Top of ridge, bears NE and SW.; descend NW slope.
79.87	Cor. secs. 7, 8, 17 and 18. Land, mountainous. Soil, rocky; 4th rate. Timber, cedar, fir, yellow pine and hemlock. Underbrush, vine maple, rhododendrons, willows, young firs and greasewood. Land mountainous, covered with dense underbrush and heavily timbered and exceptionally difficult to survey, 79.87 chs.
	June 28, 1910.
	Thence I run
	S.89*59'W., on random line, bet. secs. 7 and 18.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	Intersect N and S line, 5.42 chs. N of cor. secs. 7, 12, 13 and 18, which is a stake marked and witnessed as described by the Surveyor General. Set stone, 6x10x14 ins., 10 ins. in the ground for closing cor. secs. 7 and 18, marked CC on E face, with 2 grooves on N and 4 grooves on S face, from which