

County Surveyor's Record, Douglas County, Oregon

- 5478 $\frac{1}{2}$ -

Subdivision of T. 28 S., R. 2 W., W. Mer.

CHAINS											
40.00	<p>Set granite stone, 8 x 10 x 15 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked:</p> <p style="text-align: center;">$\frac{1}{4}$ on W. face;</p> <p>from which,</p> <p style="padding-left: 40px;">A fir, 3 ins. diam., bears S. 65°E., 15 lks. dist., marked: $\frac{1}{4}$ S 5 BT.</p> <p style="padding-left: 40px;">A fir, 3 ins. diam., bears N. 50°W., 57 lks. dist., marked: $\frac{1}{4}$ S 6 B T.</p>										
65.00	House, W. M. Robinett, bears W. 24 chs.										
74.41	Intersect N. bdy. Tp., 10 lks. E. of cor. secs. 31 and 32.										
	As this does not close within limits, I retrace my own work without finding error.										
	Thence from cor. secs. 31 and 32, I retrace East, along 6th. Standard Parallel on S. bdy. sec. 32, T.27 S., R.2 W.										
40.65	$\frac{1}{4}$ sec. cor., which is a stake mkd. and witnessed as described by the Surveyor General.										
81.29	Cor. secs. 32 and 33, which is a stake mkd. and witnessed as described by the Surveyor General.										
	Note: Distances given in this mile are the mean of two separate measurements.										
<p>Now at point of intersection:</p> <p>Set fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for closing cor. secs. 5 and 6, mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 20px;">00 T28S R2W</td> <td>on S.,</td> </tr> <tr> <td style="padding-right: 20px;">S5</td> <td>on E., and</td> </tr> <tr> <td style="padding-right: 20px;">S6</td> <td>on W. face, with</td> </tr> <tr> <td style="padding-right: 20px;">5 grooves</td> <td>on E., and</td> </tr> <tr> <td style="padding-right: 20px;">1 groove</td> <td>on W. face;</td> </tr> </table> <p>from which,</p> <p style="padding-left: 40px;">A fir, 3 ins. diam., bears S. 57°E., 81 lks. dist., mkd. T. 28 S R 2 W S 5 B T.</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears S. 45°W., 9 lks. dist., mkd. T 28 S R 2 W S 6 B T.</p> <p>Land; mountainous.</p> <p>Soil; rocky, 4th. rate.</p> <p>Timber; fir, cedar, yellow pine and hemlock.</p>		00 T28S R2W	on S.,	S5	on E., and	S6	on W. face, with	5 grooves	on E., and	1 groove	on W. face;
00 T28S R2W	on S.,										
S5	on E., and										
S6	on W. face, with										
5 grooves	on E., and										
1 groove	on W. face;										